




D – blade diameter [mm], S – tooth width [mm], s – body thickness [mm], d – bore [mm], z – number of teeth

TCT Saw Blades HANIBAL

- » longitudinal cuts of massive wood dimensions
- » machine feed

33.1 FZ




D (mm)	S (mm)	s (mm)	d (mm)	z
600	5,5	3,5	30	40
700	5,5	3,5	35	40
800	6,5	4,5	35	40

TCT Saw Blades for Wood Cutting

- » cutting along the grain of natural massive wood
- » suitable for prismatic beam saws


80 - 50 FZ



D (mm)	S (mm)	s (mm)	d (mm)	z
300	4,0	2,8	30	18
350	4,0	2,8	30	20
400	4,4	3,2	30	24
450	4,4	3,2	30	28
500	5,2	3,5	30	30
550	5,5	3,5	30	32
600	5,5	3,5	30	36

» cutting along the grain of natural massive wood

80 - 40 FZ




D (mm)	S (mm)	s (mm)	d (mm)	z
200	2,5	1,6	20	16
250	3,2	2,2	30	20
300	3,2	2,2	30	24
350	3,6	2,5	30	28
400	3,6	2,5	30	32
450	4,0	2,8	30	36
500	4,0	2,8	30	40
600	5,5	3,5	30	48
700	5,5	3,5	35	56

» cross and longitudinal cutting of natural solid wood

» maximum height of cut 150 mm

81 - 35 WZ




D (mm)	S (mm)	s (mm)	d (mm)	z
700	4,0	3,0	30	60

» cutting along and across the grain of natural massive wood

» cutting plywood, chip-board, wood – base panels


81 - 26 WZ



D (mm)	S (mm)	s (mm)	d (mm)	z
160	2,5	1,6	20	16
180	2,5	1,6	20	20
200	2,5	1,6	20	24
250	3,2	2,2	30	32
300	3,2	2,2	30	36
350	3,6	2,5	30	40
400	3,6	2,5	30	48
450	4,0	2,8	30	56
500	4,0	2,8	30	64

TCT Saw Blades for Wood Cutting


81 - 20 WZ



cutting across the grain of natural massive wood
cutting of laminated paper and laminated textiles, thermoplastics

D (mm)	S (mm)	s (mm)	d (mm)	z
160	2,5	1,6	20	24
180	2,5	1,6	20	28
200	2,5	1,6	20	32
250	3,2	2,2	30	40
300	3,2	2,2	30	48
315	3,2	2,2	30	48
350	3,6	2,5	30	54
400	3,6	2,5	30	64
450	4,0	2,8	30	72
500	4,0	2,8	30	84
600	5,2	3,5	30	90


81 - 16 WZ



D (mm)	S (mm)	s (mm)	d (mm)	z
180	2,5	1,6	20	36
200	2,5	1,6	20	40
250	3,2	2,2	30	48
300	3,2	2,2	30	60
300	3,2	2,2	30	64
350	3,6	2,5	30	72
400	3,6	2,5	30	84

» cutting across the grain of natural wood


81 - 13 WZ



D (mm)	S (mm)	s (mm)	d (mm)	z
160	2,5	1,6	20	36
200	2,5	1,6	20	48
250	3,2	2,2	30	60
250	3,2	2,2	30	64
300	3,2	2,2	30	72
350	3,6	2,5	30	84
400	3,6	2,5	30	96

81 - 11 WZ

» cutting across the grain of single-side veneered materials
surface machined
boards from natural wood and wood-base panels.



D (mm)	S (mm)	s (mm)	d (mm)	z
160	2,5	1,6	20	48
180	2,5	1,6	20	56
200	2,5	1,6	20	64
250	3,2	2,2	30	72
250	3,2	2,2	30	80
300	3,2	2,2	30	96
350	3,6	2,5	30	108
400	3,6	2,5	30	120